



AquaSafe WSL25 Pro

The AquaSafe WSL25 Pro is designed for professionals who demand the utmost in precision and functionality from their portable water quality testing equipment. This top-tier model combines all of the features of the WSL25 series with additional enhancements to handle the most demanding field conditions.

Key Features

Enhanced Photometer: Comes equipped to test essential parameters concerning water safety. Has the potential to test up to 140 parameters with additional reagents.

Comprehensive Digital Testing: Includes the high-precision AquaCheck for pH and conductivity, along with advanced sensors for an expanded range of tests.

Advanced Single Incubator: Features a sophisticated incubator that supports a wider variety of microbiological tests under optimal conditions.

Robust and Portable: Despite its comprehensive features, the WSL25 Pro maintains a compact and lightweight design, making it easy to transport and set up.

High-Capacity Battery Pack: Equipped with an enhanced battery that allows for longer field operations without the need for frequent recharging.

Superior Contamination Prevention: Utilizes the Petri-Lok[®] system to ensure sample integrity throughout the testing process.

Comprehensive Testing Parameters: Capable of testing for a wide range of water quality parameters, making it suitable for the most rigorous field conditions and compliance requirements.



Device Parameters

Microbiological: TTC (Indicator of E. coli) | Total Coliforms

Physicochemical: pH | Conductivity | TDS | Turbidity | Nitrate | Nitrite | Chlorine | Copper | Iron | Alkalinity | Hardness (Calcium & Magnesium) | Phosphate | Ammonia | Fluoride and over 100 more.

For a full list of parameters and reagents regarding the AquaPro, please scan the QR code and follow the link to the website.



AquaPro



AquaCheck

Technical Specification: Incubator

Input	12-24 V DC
Temperature Range	20°C to 50°C
Timer	24 Hour Clock
Display	LCD Display with Tactile Soft Keys
Temperature Stability	+/- 0.1°C
Petri dish Capacity	25
Power Consumption	37°C Cycle at 20°C ambient: 8.1W (max power) 3W (average consumption)
Warranty	1 Year (Excludes reagents and consumables)

Kit Hardware

- Petri-Lok Single Incubator
- AquaPro Photometer
- AquaCheck Multi-Parameter meter
- Arsenic Test Kit (Quick)
- AquaPro Reagents:300+
- Aluminium Petri Dishes: 25
- Membrane Filtration Unit

Product	Code
AquaSafe WSL25PRO	WSL25PRO

Replacement Consumables and Reagents

Part Number	Description
800155	m-Lauryl Sulphate Broth (50 tests = 7.26g)
800149	pH 4.01 Buffer Solution (60ml)
800150	pH 7.00 Buffer Solution (60ml)
800151	EC 1413 uS Calibration Solution (60ml)
951589	Ammonia LR pow (Photometer)
951593	Chroline DPD 1 + 3 (Photometer)
931037	Nitrate (Photometer)
951620	Nitrite (Photometer)

Disclaimer: Packet sizes, product availability, and part numbers may vary. Please confirm current specifications with your sales representative before ordering.



Additional Information



← Link to ASMS app via
Google Play Store

Or visit asmsonline.net

- Compatible with the AquaSafe Management Software package (ASMS).
- ASMS is a Cloud based data presentation and storage tool, with companion mobile app.
- The wealth of results can be visualised, analysed and managed to give full traceability and ensure regulatory compliance.



Trace2o, Station Road, Thatcham, Berkshire, United Kingdom, RG19 4HZ

T +44 (0)1635 866 772 | info@trace2o.com | www.trace2o.com